

SPECIFICATIONS

Modulation Input

Input Impedance
Digital Input (SMC)


75 Ohms
Standard TTL

RF Output

Center Frequency (Fc)
Output Power (SMA Female)
Rise/Fall Time
RF Contrast Ratio
Harmonic Distortion
Output Impedance
Output VSWR
Power Supply Voltage

150 MHz $\pm 0.1\%$
2.5 W
7 nsec Max
50 dB min
-20 dBc
50 Ohms
1.5 : 1 Max
+24 V @ 760 mA

OUTLINE DRAWING



Document

11/10/11

Control

Notes:

- Output power factory set to 2.5 W at 2.4 Volt input. Power stability less than 5% over the heat sink's ambient temperature range of 0 - 40° C, after 5 minute warm-up.
- When calculating the contrast ratio, it is understood that only the power of the 150 MHz fundamental shall be used. The higher harmonics have no effect on the AO modulator's performance.
- RoHS compliant

THIS DOCUMENT IS THE PROPERTY OF CRYSTAL TECHNOLOGY, LLC. IT IS NOT TO BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART OTHER THAN BY EMPLOYEES OF CRYSTAL TECHNOLOGY AND ITS CONTRACTED REPRESENTATIVES AND DISTRIBUTORS. ANY EXCEPTION REQUIRES THE WRITTEN CONSENT OF AN AUTHORIZED REPRESENTATIVE OF CRYSTAL TECHNOLOGY.

TOLERANCES: .XX $\pm .01$.XXX $\pm .005$	DR	Geri Scholz 10/27/2011	Crystal Technology, LLC		
MATERIAL:	CHK		DESCRIPTION: AODR 1150AF-DINA-2.5 HCR		
FINISH:	APP				
	APP		PART NUMBER: 97-02910-15	REV: 1	1 of 1