


## Connector Set for AOM Driver Series A35xxx and A36xxx

This accessory provides the connection of the analogue and digital modulation interface as well as the power connection for the A35xxx and A36xxx AOM driver series.

It comprises the fully shielded plug and 1 meter pigtails. For details refer to the part list below. The RF connecting cable between the RF driver and the AOM is not included.



- 1 GND (case)
- 5 +Us (24VDC)
- 2, 3, 4 not connected
- A1 Analogue modulation
- A2 Digital modulation

## **Part List**

Item	Qty.	Description	Part-No.	Manufacturer
1	1	Mixed contact Connector Sub-D 7W2	DAM-7W2P-K87	ITT Cannon
			FM7W2P-K120	FCT
2	2	Coaxial terminal pin, 50R, straight, for RG 178B/U coax cable	DM 53740-5000	ITT Cannon
			FMX005P102	FCT
3	1	Housing, shielded shell	DA 121073-150	ITT Cannon
			FKC2GA	FCT
4	2	Locking screw	250-8501-01 <b>3</b>	ITT Cannon
			FRS1/5-K190	FCT
5	2x 1.0 m	RF-Coax cable RG178B/U (A1, A2)		
6	1.0 m	Wire, H05V-K, 0.5mm <sup>2</sup> , black (Pin 1)		
7	1.0 m	Wire, H05V-K, 0.5mm <sup>2</sup> , red (Pin 5)		

## **Ordering Code**

Part-No. 508A00169