


Real deep UV Q-switched solid-state laser,
213 nm wavelength, TEM₀₀ beam profile



Applications

- Fiber Bragg grating fabrication
- Wavelength sensitive processes
- Stereo-lithography
- Display repair
- Micro-machining
- Semi-conductor inspection
- Replacement of freq. doubled Ar-Ion lasers
- Photoluminescence measurements

Features

- Extremely short UV wavelength
- Diode laser pumped
- Slot mounted laser diode
- Excellent beam profile
- High pulse power
- Ultra low maintenance costs
- "Green Photonics"
- 24/7 continuous industrial use

General Description

The IMPRESS 213 laser system is a high repetition rate solid-state diode pumped Q-switched laser with an emission wavelength of 213 nm. Its precise TEM₀₀-mode laser beam is well suited for metrology and micro-machining such as semi-conductor or display repair. Due to the very short wavelength structure sizes below 1 μm are possible in direct writing applications. The laser delivers < 7 ns short pulses with a superior beam quality of $M^2 < 1.6$. The laser system is completely computer controlled via a RS-232 interface. Different trigger control modes are available. The system operates autoranging from 90-240 VAC, 47-63 Hz.


Product Specifications

Model	IMPRESS 213
wavelength	213 nm
average power	100 mW
pulse duration	< 7 ns
energy per pulse	> 10 μJ
repetition rate	0.1-30 kHz
M^2	< 1.6

Specifications are subject to change without notice due to product improvement.

Outstanding in FBG writing

- Extremely fast writing
- No Hydrogen loading necessary





System Dimensions (L x W x H), weight

Laser head	500 x 390 x 118 mm ³	21 kg
Power supply	446 x 440 x 134 mm ³	16.8 kg
Chiller	446 x 440 x 134 mm ³	18.5 kg

Electrical Characteristics


Operating voltage	85-264 VAC
Frequency	47 – 63 Hz
Power consumption	300 W typ.

Typical Performance



Dimensions Laser Head


Front view



Side view



Top view



Visible and/or invisible
laser radiation. Avoid eye
or skin exposure to direct
or scattered radiation.
Class 4 laser (IEC-825)



Xiton Photonics GmbH
Kohlenhofstrasse 10
D-67663 Kaiserslautern
Germany

Tel.: +49 (0)631 414 9944-0
Fax: +49 (0)631 414 9944-9
sales@xiton-photonics.com
www.xiton-photonics.com